

U.S. Serial No.: 10/629,978  
Filed: July 30, 2003  
Group Art Unit: 3739  
Examiner: Pctor J. Vrettakos  
Atty. Docket No.: 22956-234

### AMENDMENTS TO THE CLAIMS

1-27. (Cancelled).

28-37. (Cancelled).

38. (Currently Amended) A device for anchoring a filament to tissue or bone, comprising:  
an anchoring element adapted to be embedded in bone and having a cavity formed therein;  
and

an insertion stem adapted to be disposed in the cavity to retain a filament between the insertion stem and the anchoring element, the insertion stem including at least one radial channel ~~formed around~~ extending through a head thereof and at least one suture-receiving channel formed on a surface thereof and adapted to slidably receive a filament, the suture-receiving channel having a size adapted such that the filament is retained by compression fit between the insertion stem and the anchoring element when the insertion stem is disposed within the cavity in the anchoring element.

39. (Previously Presented) The device of claim 38, wherein the cavity comprises a lumen extending between proximal and distal ends of the anchoring element.

40. (Previously Presented) The device of claim 39, where the insertion stem includes at least one suture-receiving channel that extends between proximal and distal ends thereof.

41. (Cancelled).

42. (Previously Presented) The device of claim 39, further comprising at least one filament disposed within the at least one suture-receiving channel.

43. (Previously Presented) The device of claim 42, wherein the filament is non-movable when the insertion stem is disposed in the cavity in the anchoring element.

U.S. Serial No.: 10/629,978  
Filed: July 30, 2003  
Group Art Unit: 3739  
Examiner: Peter J. Vrettakos  
Atty. Docket No.: 22956-234

44. (Previously Presented) The device of claim 38, wherein the anchoring element is adapted to be embedded in a tunnel in bone.
45. (Previously Presented) The device of claim 38, wherein the insertion stem has an outer diameter that is equal to or greater than an inner diameter of the cavity in the anchoring element.
46. (Previously Presented) The device of claim 38, wherein the device is formed from a biocompatible material selected from the group consisting of polyethylene, polypropylene, steel, poly-L-lactide and lactide-glycolide compositions.
47. (Currently Amended) A device for anchoring a filament to tissue or bone, comprising:  
an anchor member adapted to be embedded in bone, the anchor having at least one cavity therein and including first and second components adapted to be held together solely by interference fit when held a filament is disposed therebetween ~~by interference fit~~ such that, where the filament has a breaking strength greater than a threshold force, the filament is substantially non-movable in response to a tensional force less than a threshold force applied to the filament, and the filament is longitudinally movable in response to a tensional force greater than the threshold force applied to the filament.
48. (Cancelled).
49. (Currently Amended) A device for anchoring a filament to tissue or bone, comprising:  
an anchor member adapted to be embedded in bone, the anchor having at least one cavity therein and first and second components that are adapted to be held together solely by interference fit when held a filament is disposed within the at least one cavity ~~by an interference fit~~ between the first and second components such that the filament is effective to resist operational forces to which the filament is subjected to subsequent to deployment of the device into bone.
50. (Previously Presented) The device of claim 49, wherein the anchor member includes a frangible portion that is adapted to shear during deployment of the device into bone.

U.S. Serial No.: 10/629,978  
Filed: July 30, 2003  
Group Art Unit: 3739  
Examiner: Peter J. Vrettakos  
Atty. Docket No.: 22956-234

51. (Previously Presented) The device of claim 49, wherein the at least one cavity includes opposite open ends.
52. (Currently Amended) A device for anchoring a filament to tissue or bone, comprising:  
a first component adapted to be embedded in bone and having at least one cavity therein;  
a second component receivable within the first component such that the first and second components are held together solely by interference fit when effective to retain a filament is disposed therebetween by interference fit.
53. (Previously Presented) The device of claim 52, wherein the first and second components are adapted to hold the filament such that, where the filament has a breaking strength greater than the threshold force, the filament is substantially non-movable in response to a tensional force less than a threshold force applied to at least one portion of the filament, and the filament is longitudinally movable in response to a tensional force greater than the threshold force applied to the at least one portion of the filament.
54. (Previously Presented) The device of claim 52, wherein the first and second components are adapted to hold the filament such that the filament is effective to resist operational forces to which the filament is subjected to subsequent to deployment of the device in a patient's body.
55. (Previously Presented) The device of claim 52, wherein the first anchor member includes a frangible portion that is adapted to shear during deployment of the device into bone.
56. (Previously Presented) The device of claim 52, wherein the at least one cavity component includes opposite open ends.
57. (Currently Amended) A device for anchoring a filament to tissue or bone, comprising:  
an anchor member adapted to be embedded in bone and having a cavity formed therein and  
an insertion element adapted to be disposed in the cavity in the anchor member, the anchor member and the insertion element being held together solely adapted to hold a filament within the cavity by interference fit when a filament is disposed within the cavity.

U.S. Serial No.: 10/629,978  
Filed: July 30, 2003  
Group Art Unit: 3739  
Examiner: Peter J. Vrettakos  
Atty. Docket No.: 22956-234

58-67. (Cancelled).

68. (Previously Presented) A suture anchor, comprising:  
an elongate shaft having an insertion element frangibly attached to a distal end thereof; and  
an anchoring element adapted to be disposed within bone and to receive the insertion element  
such that the insertion element and the anchoring element are adapted to retain a suture therebetween  
by an interference fit.

69. (Previously Presented) The device of claim 68, wherein the insertion element includes a  
flange formed on a terminal end thereof and adapted to abut a terminal end of the anchoring element.

70. (Previously Presented) The device of claim 68, wherein the anchoring element includes a  
cavity formed therein for receiving the insertion element.

71. (Previously Presented) The device of claim 70, further comprising a filament extending  
through the cavity in the anchoring element between the anchoring element and insertion element.

72. (Currently Amended) A suture anchor, comprising:  
an elongate anchor member adapted to be embedded in bone and having a cavity extending  
therethrough with opposite open ends;  
an elongate insertion element adapted to be disposed in the cavity in the anchor member; and  
a suture extending through the cavity in the anchor member between the opposite open ends,  
forming a loop segment, and passing back through the cavity, at least a portion of the suture being  
~~positioned between the anchor member and the insertion element~~ such that the suture is held  
therebetween by a compression fit.

73. (Previously Presented) A suture anchor, comprising:  
an insertion element having an elongate shaft frangibly attached to a distal end thereof; and  
an anchoring element adapted to be disposed within bone and having a cavity extending  
therethrough between opposite open ends thereof for receiving the insertion element such that the  
insertion element and the anchoring element are adapted to retain a suture therebetween.